

Airtec XLK 40/160. ISO 15552 cylinders, piston 40 mm, stroke 160 mm

Item no.	FL-XLK-40/160	Manufacturer	Airtec
Manufacturer no.	XLK 40/160	EAN	4050571801960

ISO 15552 cylinders, piston 40 mm, stroke 160 mm

TECHNICAL DATA

Article authenticity	Original product
Condition of article	New
HS-Code	84123100
Weight	19 kg



STANDARDS & COMPLIANCE

ISO 15552

DESCRIPTION

Materials:

Head and foot: stove-enamelled die-cast aluminium, cylinder tube: anodized aluminium profile tube, piston rod: hard chromium plated steel, piston: complete piston (ST / NBR), seal: NBR / PUR

Temperature range:

-20°C to +80°C

Operating pressure:

max. 10 bar

Optional:

FKM seals (temperature range: -10°C to max. +150°C, without magnetic piston) **-V**, stainless steel piston rod **-EK**, ATEX approval Ex II 2GD c T5 T100° -20°C ≤ Ta ≤ 80°C **-X**

Version:

with magnetic pistons and adjustable end position damping

Cylinder switch type:

D, A

Piston diameter [mm]	40
Stroke [mm]	160
Version	continuous piston rod
A (thread)	M 12x1,25
G (compressed air port)	G 1/4"
Repair sets	XL 40 REP
B [mm]	16
C [mm]	35
D [mm]	22,0
F [mm]	24
G [mm]	30
H [mm]	135
K [mm]	4
M [mm]	54,0
N [mm]	38,0
CH [mm]	13
RT	M 6