

Airtec XLK 50/100. ISO 15552 cylinders, piston 50 mm, stroke 100 mm

Item no. FL-XLK-50/100

Manufacturer Airtec

EAN 4050571802059

ISO 15552 cylinders, piston 50 mm, stroke 100 mm

TECHNICAL DATA

HS-Code 84123100

Weight 2.4 kg



STANDARDS & COMPLIANCE

ISO 15552

DESCRIPTION

Materials:

Head and foot: stove-enamelled die-cast aluminium, cylinder tube: anodized aluminium profile tube, piston rod: hard chromium plated steel, piston: complete piston (ST / NBR), seal: NBR / PUR

Temperature range:

-20°C to +80°C

Operating pressure:

max. 10 bar

Optional:

FKM seals (temperature range: -10°C to max. +150°C, without magnetic piston) **-V**, stainless steel piston rod **-EK**, ATEX approval Ex II 2GD c T5 T100° -20°C ≤ Ta ≤ 80°C **-X**

Version:

with magnetic pistons and adjustable end position damping

Cylinder switch type:

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

D, A

Piston diameter [mm]	50
Stroke [mm]	100
Version	continuous piston rod
A (thread)	M 16x1,5
G (compressed air port)	G 1/4"
Repair sets	XL 50 REP
B [mm]	20
C [mm]	40
D [mm]	25,5
F [mm]	32
G [mm]	37
H [mm]	143
K [mm]	4
M [mm]	63,0
N [mm]	46,5
CH [mm]	17
RT	M 8