

# Airtec XLK 63/250. ISO 15552 cylinders, piston 63 mm, stroke 250 mm

<b>Item no.</b>	FL-XLK-63/250	<b>Manufacturer</b>	Airtec
<b>Manufacturer no.</b>	XLK 63/250	<b>EAN</b>	4050571802219

ISO 15552 cylinders, piston 63 mm, stroke 250 mm

## TECHNICAL DATA

Article authenticity	<b>Original product</b>
Condition of article	<b>New</b>
HS-Code	<b>84123100</b>
Weight	<b>43 kg</b>



## STANDARDS & COMPLIANCE

**ISO 15552**

## DESCRIPTION

Materials:

Head and foot: stove-enamelled die-cast aluminium, cylinder tube: anodized aluminium profile tube, piston rod: hard chromium plated steel, piston: complete piston (ST / NBR), seal: NBR / PUR

Temperature range:

-20°C to +80°C

Operating pressure:

max. 10 bar

Optional:

FKM seals (temperature range: -10°C to max. +150°C, without magnetic piston) **-V**, stainless steel piston rod **-EK**, ATEX approval Ex II 2GD c T5 T100° -20°C ≤ Ta ≤ 80°C **-X**

Version:

with magnetic pistons and adjustable end position damping

Cylinder switch type:

D, A

Piston diameter [mm]	63
Stroke [mm]	250
Version	continuous piston rod
A (thread)	M 16x1,5
G (compressed air port)	G 3/8"
Repair sets	<a href="#">XL 63 REP</a>
B [mm]	20
C [mm]	45
D [mm]	25,0
F [mm]	32
G [mm]	37
H [mm]	158
K [mm]	4
M [mm]	74,0
N [mm]	56,5
CH [mm]	17
RT	M 8