

Airtec XLK 80/25. ISO 15552 cylinders, piston 80 mm, stroke 25 mm

Item no. FL-XLK-80/25

Manufacturer Airtec

EAN 4050571802318

ISO 15552 cylinders, piston 80 mm, stroke 25 mm

TECHNICAL DATA

HS-Code **84123100**Weight **1 kg**

STANDARDS & COMPLIANCE

ISO 15552

DESCRIPTION

Materials:

Head and foot: stove-enamelled die-cast aluminium, cylinder tube: anodized aluminium profile tube, piston rod: hard chromium plated steel, piston: complete piston (ST / NBR), seal: NBR / PUR

Temperature range:

-20°C to +80°C

Operating pressure:

max. 10 bar

Optional:

FKM seals (temperature range: -10°C to max. +150°C, without magnetic piston) **-V**, stainless steel piston rod **-EK**, ATEX approval Ex II 2GD c T5 T100° -20°C ≤ Ta ≤ 80°C **-X**

Version:

with magnetic pistons and adjustable end position damping

Cylinder switch type:

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

D, A

Piston diameter [mm]	80
Stroke [mm]	25
Version	continuous piston rod
A (thread)	M 20x1,5
G (compressed air port)	G 3/8"
Repair sets	XL 80 REP
B [mm]	25
C [mm]	45
D [mm]	35,0
F [mm]	40
G [mm]	46
H [mm]	174
K [mm]	4
M [mm]	93,5
N [mm]	72,0
CH [mm]	22
RT	M 10