

Airtec ZDM 10/125. ISO 6432 cylinders, double acting, piston 10 mm, stroke 125 mm

Item no. FL-ZDM-10/125

Manufacturer Airtec

EAN 4050571811174

ISO 6432 cylinders, double acting, piston 10 mm, stroke 125 mm

TECHNICAL DATA

HS-Code 84123100

Weight 0.075 kg



STANDARDS & COMPLIANCE

ISO 6432

DESCRIPTION

Materials:

Head and foot: anodized aluminium, cylinder tube: 1.4301, piston rod: 1.4305 seal: NBR / PUR

Temperature range:

-20°C to +80°C

Operating pressure:

max. 10 bar

Version:

With Magnetic piston

Cylinder switch type:

D in combination with fastening D1, C in combination with fastening C1

Optional:

FKM seals (temperature range: -20°C to max. +150°C, without magnetic piston) **-V**, ATEX approvalEx II 2GD c T5 T100° -20°C ≤ Ta ≤ 80°C **-X**

Piston diameter [mm]	10
Stroke [mm]	125
Version	Standard
A (piston rod thread)	M 4
B (fastening thread)	M 12x1,25
G (compressed air port)	M 5
A1 [mm]	4
C [mm]	16
D [mm]	8
E [mm]	4
F [mm]	12
G [mm]	64
K [mm]	16
L [mm]	12
M [mm]	86
N [mm]	6
P [mm]	46