

Airtec ZDM 16/25. ISO 6432 cylinders, double acting, piston 16 mm, stroke 25 mm

Item no.	FL-ZDM-16/25	Manufacturer	Airtec
Manufacturer no.	ZDM 16/25	EAN	4050571811440

ISO 6432 cylinders, double acting, piston 16 mm, stroke 25 mm

TECHNICAL DATA

Article authenticity	Original product
Condition of article	New
HS-Code	84123100
Weight	1 kg



STANDARDS & COMPLIANCE

ISO 6432

DESCRIPTION

Materials:

Head and foot: anodized aluminium, cylinder tube: 1.4301, piston rod: 1.4305 seal: NBR / PUR

Temperature range:

-20°C to +80°C

Operating pressure:

max. 10 bar

Version:

With Magnetic piston

Cylinder switch type:

D in combination with fastening D1, C in combination with fastening C1

Optional:

FKM seals (temperature range: -20°C to max. +150°C, without magnetic piston) **-V**, ATEX approval

Ex II 2GD c T5 T100° -20°C ≤Ta≤ 80°C -X

Piston diameter [mm]	16
Stroke [mm]	25
Version	Standard
A (piston rod thread)	M 6
B (fastening thread)	M 16x1,5
G (compressed air port)	M 5
A1 [mm]	6
C [mm]	19
D [mm]	12
E [mm]	6
F [mm]	16
G [mm]	82
K [mm]	22
L [mm]	18
M [mm]	109
N [mm]	9
P [mm]	53
CH [mm]	5