

Airtec ZDM 20/40 ES. ISO 6432 cylinders, stainless steel, piston 20 mm, stroke 40 mm

Item no. FL-ZDM-20/40-ES

Manufacturer Airtec

EAN 4050571811846

ISO 6432 cylinders, stainless steel, piston 20 mm, stroke 40 mm

TECHNICAL DATA

Colour **Stainless Steel**HS-Code **84123100**Weight **0.34 kg**

STANDARDS & COMPLIANCE

ISO 6432

DESCRIPTION

Materials:

Head and foot: 1.4301, cylinder tube: 1.4301, piston rod: 1.4436, seals: NBR / PUR

Temperature range:

-20°C to +80°C

Operating pressure:

max. 10 bar

Version:

With Magnetic piston

Cylinder switch type:

C in combination with mounting E1

Optional:

FKM seals (temperature range: -20°C to max. +150°C, without magnetic piston) **-V**

Piston diameter [mm]	20
Stroke [mm]	40
Version	Standard
A (piston rod thread)	M 8
B (fastening thread)	M 22x1,5
G (compressed air port)	G 1/8"
A1 [mm]	8
C [mm]	27
D [mm]	16
E [mm]	8
F [mm]	20
G [mm]	95
K [mm]	24
L [mm]	20
M [mm]	131
N [mm]	12
P [mm]	67
CH [mm]	7