

Airtec ZDM 25/10 ES. ISO 6432 cylinders, stainless steel, piston 25 mm, stroke 10 mm

Item no. FL-ZDM-25/10-ES

Manufacturer Airtec

EAN 4050571811983

ISO 6432 cylinders, stainless steel, piston 25 mm, stroke 10 mm

TECHNICAL DATA

Colour **Stainless Steel**

HS-Code **84123100**

Weight **0.42 kg**



STANDARDS & COMPLIANCE

ISO 6432

DESCRIPTION

Materials:

Head and foot: 1.4301, cylinder tube: 1.4301, piston rod: 1.4436, seals: NBR / PUR

Temperature range:

-20°C to +80°C

Operating pressure:

max. 10 bar

Version:

With Magnetic piston

Cylinder switch type:

C in combination with mounting E1

Optional:

FKM seals (temperature range: -20°C to max. +150°C, without magnetic piston) **-V**

Piston diameter [mm]	25
Stroke [mm]	10
Version	Standard
A (piston rod thread)	M 10x1,25
B (fastening thread)	M 22x1,5
G (compressed air port)	G 1/8"
A1 [mm]	10
C [mm]	30
D [mm]	16
E [mm]	8
F [mm]	22
G [mm]	104
K [mm]	28
L [mm]	22
M [mm]	140
N [mm]	12
P [mm]	68
CH [mm]	9