

# Airtec ZDMK 16/100 ES. ISO 6432 cylinders, stainless steel, piston 16 mm, stroke 100 mm

<b>Item no.</b>	<b>FL-ZDMK-16/100-ES</b>	<b>Manufacturer</b>	<b>Airtec</b>
<b>Manufacturer no.</b>	<b>ZDMK 16/100 ES</b>	<b>EAN</b>	<b>4050571812454</b>

ISO 6432 cylinders, stainless steel, piston 16 mm, stroke 100 mm

## TECHNICAL DATA

Article authenticity	<b>Original product</b>
Colour	<b>Stainless Steel</b>
Condition of article	<b>New</b>
HS-Code	<b>84123100</b>
Weight	<b>1 kg</b>



## STANDARDS & COMPLIANCE

**ISO 6432**

## DESCRIPTION

Materials:

Head and foot: 1.4301, cylinder tube: 1.4301, piston rod: 1.4436, seals: NBR / PUR

Temperature range:

-20°C to +80°C

Operating pressure:

max. 10 bar

Version:

With Magnetic piston

Cylinder switch type:

C in combination with mounting E1

Optional:

FKM seals (temperature range: -20°C to max. +150°C, without magnetic piston) -V

Piston diameter [mm]	16
Stroke [mm]	100
Version	continuous piston rod
A (piston rod thread)	M 6
B (fastening thread)	M 16x1,5
G (compressed air port)	M 5
A1 [mm]	6
C [mm]	19
D [mm]	12
E [mm]	6
F [mm]	16
G [mm]	82
K [mm]	22
L [mm]	18
M [mm]	109
N [mm]	9
P [mm]	53
CH [mm]	5