

Airtec ZDMK 16/25 ES. ISO 6432 cylinders, stainless steel, piston 16 mm, stroke 25 mm

Item no. FL-ZDMK-16/25-ES

Manufacturer Airtec

EAN 4050571812560

ISO 6432 cylinders, stainless steel, piston 16 mm, stroke 25 mm

TECHNICAL DATA

Colour **Stainless Steel**HS-Code **84123100**Weight **1 kg**

STANDARDS & COMPLIANCE

ISO 6432

DESCRIPTION

Materials:

Head and foot: 1.4301, cylinder tube: 1.4301, piston rod: 1.4436, seals: NBR / PUR

Temperature range:

-20°C to +80°C

Operating pressure:

max. 10 bar

Version:

With Magnetic piston

Cylinder switch type:

C in combination with mounting E1

Optional:

FKM seals (temperature range: -20°C to max. +150°C, without magnetic piston) **-V**

Piston diameter [mm]	16
Stroke [mm]	25
Version	continuous piston rod
A (piston rod thread)	M 6
B (fastening thread)	M 16x1,5
G (compressed air port)	M 5
A1 [mm]	6
C [mm]	19
D [mm]	12
E [mm]	6
F [mm]	16
G [mm]	82
K [mm]	22
L [mm]	18
M [mm]	109
N [mm]	9
P [mm]	53
CH [mm]	5