

## Airtec ZDMO 20/10. ISO 6432 cylinders, double acting, piston 20 mm, stroke 10 mm

Item no. FL-ZDMO-20/10

Manufacturer Airtec

EAN 4050571813284

ISO 6432 cylinders, double acting, piston 20 mm, stroke 10 mm

### TECHNICAL DATA

HS-Code 84123100

Weight 1 kg



### STANDARDS & COMPLIANCE

ISO 6432

### DESCRIPTION

Materials:

Head and foot: anodized aluminium, cylinder tube: 1.4301, piston rod: 1.4305 seal: NBR / PUR

Temperature range:

-20°C to +80°C

Operating pressure:

max. 10 bar

Version:

With Magnetic piston

Cylinder switch type:

D in combination with fastening D1, C in combination with fastening C1

Optional:

FKM seals (temperature range: -20°C to max. +150°C, without magnetic piston) **-V**, ATEX approvalEx II 2GD c T5 T100° -20°C ≤ Ta ≤ 80°C **-X**

|                         |                                     |
|-------------------------|-------------------------------------|
| Piston diameter [mm]    | 20                                  |
| Stroke [mm]             | 10                                  |
| Version                 | non-rotating piston rod (hexagonal) |
| A (piston rod thread)   | M 8                                 |
| B (fastening thread)    | M 22x1,5                            |
| G (compressed air port) | G 1/8"                              |
| A1 [mm]                 | 8                                   |
| C [mm]                  | 27                                  |
| D [mm]                  | 16                                  |
| E [mm]                  | 8                                   |
| F [mm]                  | 20                                  |
| G [mm]                  | 95                                  |
| K [mm]                  | 24                                  |
| L [mm]                  | 20                                  |
| M [mm]                  | 131                                 |
| N [mm]                  | 12                                  |
| P [mm]                  | 67                                  |
| CH [mm]                 | 7                                   |