

# Airtec ZDMO 20/40. ISO 6432 cylinders, double acting, piston 20 mm, stroke 40 mm

<b>Item no.</b>	<b>FL-ZDMO-20/40</b>	<b>Manufacturer</b>	<b>Airtec</b>
<b>Manufacturer no.</b>	<b>ZDMO 20/40</b>	<b>EAN</b>	<b>4050571813369</b>

ISO 6432 cylinders, double acting, piston 20 mm, stroke 40 mm

## TECHNICAL DATA

Article authenticity	<b>Original product</b>
Condition of article	<b>New</b>
HS-Code	<b>84123100</b>
Weight	<b>1 kg</b>



## STANDARDS & COMPLIANCE

**ISO 6432**

## DESCRIPTION

Materials:

Head and foot: anodized aluminium, cylinder tube: 1.4301, piston rod: 1.4305 seal: NBR / PUR

Temperature range:

-20°C to +80°C

Operating pressure:

max. 10 bar

Version:

With Magnetic piston

Cylinder switch type:

D in combination with fastening D1, C in combination with fastening C1

Optional:

FKM seals (temperature range: -20°C to max. +150°C, without magnetic piston) **-V**, ATEX approval

Ex II 2GD c T5 T100° -20°C ≤Ta≤ 80°C -X

Piston diameter [mm]	20
Stroke [mm]	40
Version	non-rotating piston rod (hexagonal)
A (piston rod thread)	M 8
B (fastening thread)	M 22x1,5
G (compressed air port)	G 1/8"
A1 [mm]	8
C [mm]	27
D [mm]	16
E [mm]	8
F [mm]	20
G [mm]	95
K [mm]	24
L [mm]	20
M [mm]	131
N [mm]	12
P [mm]	67
CH [mm]	7