

Airtec ZDPM 16/160. ISO 6432 cylinders, double acting, piston 16 mm, stroke 160 mm

| | | | |
|-------------------------|-----------------------|---------------------|----------------------|
| Item no. | FL-ZDPM-16/160 | Manufacturer | Airtec |
| Manufacturer no. | ZDPM 16/160 | EAN | 4050571813819 |

ISO 6432 cylinders, double acting, piston 16 mm, stroke 160 mm

TECHNICAL DATA

| | |
|----------------------|-------------------------|
| Article authenticity | Original product |
| Condition of article | New |
| HS-Code | 84123100 |
| Weight | 165 kg |



STANDARDS & COMPLIANCE

ISO 6432

DESCRIPTION

Materials:

Head and foot: anodized aluminium, cylinder tube: 1.4301, piston rod: 1.4305 seal: NBR / PUR

Temperature range:

-20°C to +80°C

Operating pressure:

max. 10 bar

Version:

With Magnetic piston

Cylinder switch type:

D in combination with fastening D1, C in combination with fastening C1

Optional:

FKM seals (temperature range: -20°C to max. +150°C, without magnetic piston) **-V**, ATEX approval

Ex II 2GD c T5 T100° -20°C ≤Ta≤ 80°C -X

| | |
|-------------------------|---------------------------------|
| Piston diameter [mm] | 16 |
| Stroke [mm] | 160 |
| Version | adjustable end position damping |
| A (piston rod thread) | M 6 |
| B (fastening thread) | M 16x1,5 |
| G (compressed air port) | M 5 |
| A1 [mm] | 6 |
| C [mm] | 19 |
| D [mm] | 12 |
| E [mm] | 6 |
| F [mm] | 16 |
| G [mm] | 82 |
| K [mm] | 22 |
| L [mm] | 18 |
| M [mm] | 109 |
| N [mm] | 9 |
| P [mm] | 53 |
| CH [mm] | 5 |