

Airtec ZDPMK 20/320. ISO 6432 cylinders, double acting, piston 20 mm, stroke 320 mm

Item no. FL-ZDPMK-20/320

Manufacturer Airtec

EAN 4050571815165

ISO 6432 cylinders, double acting, piston 20 mm, stroke 320 mm

TECHNICAL DATA

HS-Code 84123100

Weight 1 kg



STANDARDS & COMPLIANCE

ISO 6432

DESCRIPTION

Materials:

Head and foot: anodized aluminium, cylinder tube: 1.4301, piston rod: 1.4305 seal: NBR / PUR

Temperature range:

-20°C to +80°C

Operating pressure:

max. 10 bar

Version:

With Magnetic piston

Cylinder switch type:

D in combination with fastening D1, C in combination with fastening C1

Optional:

FKM seals (temperature range: -20°C to max. +150°C, without magnetic piston) **-V**, ATEX approvalEx II 2GD c T5 T100° -20°C ≤ Ta ≤ 80°C **-X**

Piston diameter [mm]	20
Stroke [mm]	320
Version	adjustable end position damping, continuous piston rod
A (piston rod thread)	M 8
B (fastening thread)	M 22x1,5
G (compressed air port)	G 1/8"
A1 [mm]	8
C [mm]	27
D [mm]	16
E [mm]	8
F [mm]	20
G [mm]	95
K [mm]	24
L [mm]	20
M [mm]	131
N [mm]	12
P [mm]	67
CH [mm]	7