

# Airtec ZDPMK 25/200. ISO 6432 cylinders, double acting, piston 25 mm, stroke 200 mm

|                         |                        |                     |                      |
|-------------------------|------------------------|---------------------|----------------------|
| <b>Item no.</b>         | <b>FL-ZDPMK-25/200</b> | <b>Manufacturer</b> | <b>Airtec</b>        |
| <b>Manufacturer no.</b> | <b>ZDPMK 25/200</b>    | <b>EAN</b>          | <b>4050571815264</b> |

ISO 6432 cylinders, double acting, piston 25 mm, stroke 200 mm

## TECHNICAL DATA

|                      |                         |
|----------------------|-------------------------|
| Article authenticity | <b>Original product</b> |
| Condition of article | <b>New</b>              |
| HS-Code              | <b>84123100</b>         |
| Weight               | <b>1 kg</b>             |



## STANDARDS & COMPLIANCE

**ISO 6432**

## DESCRIPTION

Materials:

Head and foot: anodized aluminium, cylinder tube: 1.4301, piston rod: 1.4305 seal: NBR / PUR

Temperature range:

-20°C to +80°C

Operating pressure:

max. 10 bar

Version:

With Magnetic piston

Cylinder switch type:

D in combination with fastening D1, C in combination with fastening C1

Optional:

FKM seals (temperature range: -20°C to max. +150°C, without magnetic piston) **-V**, ATEX approval

Ex II 2GD c T5 T100° -20°C ≤Ta≤ 80°C -X

|                         |  |
|-------------------------|--|
| Piston diameter [mm]    | 25   |
| Stroke [mm]             | 200  |
| Version                 | adjustable end position damping, continuous piston rod |
| A (piston rod thread)   | M 10x1,25  |
| B (fastening thread)    | M 22x1,5   |
| G (compressed air port) | G 1/8"   |
| A1 [mm]                 | 10   |
| C [mm]                  | 30   |
| D [mm]                  | 16   |
| E [mm]                  | 8  |
| F [mm]                  | 22   |
| G [mm]                  | 104  |
| K [mm]                  | 28   |
| L [mm]                  | 22   |
| M [mm]                  | 140  |
| N [mm]                  | 12   |
| P [mm]                  | 68   |
| CH [mm]                 | 9  |