

Airtec ZEM 10/10. ISO 6432 cylinders, single acting, piston 10 mm, stroke 10 mm

| | | | |
|-------------------------|--------------|---------------------|---------------|
| Item no. | FL-ZEM-10/10 | Manufacturer | Airtec |
| Manufacturer no. | ZEM 10/10 | EAN | 4050571815578 |

ISO 6432 cylinders, single acting, piston 10 mm, stroke 10 mm

TECHNICAL DATA

| | |
|----------------------|-------------------------|
| Article authenticity | Original product |
| Condition of article | New |
| HS-Code | 84123100 |
| Weight | 47 kg |



STANDARDS & COMPLIANCE

ISO 6432

DESCRIPTION

Materials:

Head and foot: anodized aluminium, cylinder tube: 1.4301, piston rod: 1.4305 seal: NBR / PUR

Temperature range:

-20 to +80 °C

Operating pressure:

max. 10 bar

Version:

With Magnetic piston

Cylinder switch type:

D in combination with fastening D1, C in combination with fastening C1

| | |
|-----------------------|-----------|
| Piston diameter [mm] | 10 |
| Stroke [mm] | 10 |
| A (piston rod thread) | M 4 |
| B (fastening thread) | M 12x1,25 |

esd.equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com

esd.equipment

Page 1/2

G (compressed air port) M 5

| | |
|---------|----|
| A1 [mm] | 4 |
| C [mm] | 16 |
| D [mm] | 8 |
| E [mm] | 4 |
| F [mm] | 12 |
| G [mm] | 64 |
| K [mm] | 16 |
| L [mm] | 12 |
| M [mm] | 86 |
| N [mm] | 6 |
| P [mm] | 46 |