

Airtec ZEM 12/10. ISO 6432 cylinders, single acting, piston 12 mm, stroke 10 mm

Item no. FL-ZEM-12/10

Manufacturer Airtec

EAN 4050571815615

ISO 6432 cylinders, single acting, piston 12 mm, stroke 10 mm

TECHNICAL DATA

HS-Code 84123100

Weight 0.075 kg



STANDARDS & COMPLIANCE

ISO 6432

DESCRIPTION

Materials:

Head and foot: anodized aluminium, cylinder tube: 1.4301, piston rod: 1.4305 seal: NBR / PUR

Temperature range:

-20 to +80 °C

Operating pressure:

max. 10 bar

Version:

With Magnetic piston

Cylinder switch type:

D in combination with fastening D1, C in combination with fastening C1

Piston diameter [mm] 12

Stroke [mm] 10

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

A (piston rod thread)	M 6
B (fastening thread)	M 16x1,5
G (compressed air port)	M 5
A1 [mm]	6
C [mm]	19
D [mm]	12
E [mm]	6
F [mm]	16
G [mm]	75
K [mm]	22
L [mm]	18
M [mm]	104
N [mm]	9
P [mm]	48
CH [mm]	5