

# Airtec ZEM 12/25. ISO 6432 cylinders, single acting, piston 12 mm, stroke 25 mm

<b>Item no.</b>	FL-ZEM-12/25	<b>Manufacturer</b>	Airtec
<b>Manufacturer no.</b>	ZEM 12/25	<b>EAN</b>	4050571815639

ISO 6432 cylinders, single acting, piston 12 mm, stroke 25 mm

## TECHNICAL DATA

Article authenticity	<b>Original product</b>
Condition of article	<b>New</b>
HS-Code	<b>84123100</b>
Weight	<b>8 kg</b>



## STANDARDS & COMPLIANCE

**ISO 6432**

## DESCRIPTION

Materials:

Head and foot: anodized aluminium, cylinder tube: 1.4301, piston rod: 1.4305 seal: NBR / PUR

Temperature range:

-20 to +80 °C

Operating pressure:

max. 10 bar

Version:

With Magnetic piston

Cylinder switch type:

D in combination with fastening D1, C in combination with fastening C1

Piston diameter [mm]	12
Stroke [mm]	25
A (piston rod thread)	M 6
B (fastening thread)	M 16x1,5

### esd.equipment

Keldersstr. 15  
42697 Solingen, Deutschland  
VAT ID: DE269659389

Phone: +49 212 38340680  
shop@esd-equipment.com

**esd.equipment**

Page 1/2

G (compressed air port) M 5

A1 [mm]	6
C [mm]	19
D [mm]	12
E [mm]	6
F [mm]	16
G [mm]	75
K [mm]	22
L [mm]	18
M [mm]	104
N [mm]	9
P [mm]	48
CH [mm]	5