

Airtec ZEM 25/25. ISO 6432 cylinders, single acting, piston 25 mm, stroke 25 mm

Item no. FL-ZEM-25/25

Manufacturer Airtec

EAN 4050571815790

ISO 6432 cylinders, single acting, piston 25 mm, stroke 25 mm

TECHNICAL DATA

HS-Code 84123100

Weight 0.27 kg



STANDARDS & COMPLIANCE

ISO 6432

DESCRIPTION

Materials:

Head and foot: anodized aluminium, cylinder tube: 1.4301, piston rod: 1.4305 seal: NBR / PUR

Temperature range:

-20 to +80 °C

Operating pressure:

max. 10 bar

Version:

With Magnetic piston

Cylinder switch type:

D in combination with fastening D1, C in combination with fastening C1

Piston diameter [mm]	25
----------------------	----

Stroke [mm]	25
-------------	----

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

A (piston rod thread)	M 10x1,25
B (fastening thread)	M 22x1,5
G (compressed air port)	G 1/8"
A1 [mm]	10
C [mm]	30
D [mm]	16
E [mm]	8
F [mm]	22
G [mm]	104
K [mm]	28
L [mm]	22
M [mm]	140
N [mm]	12
P [mm]	68
CH [mm]	9