

# EMC ELS 6/50-AS. Compact carriages, pistons 6mm, stroke 50mm, with stroke limitation for deploying (fixed stop)

<b>Item no.</b>	FL-ELS-6/50-AS	<b>Manufacturer</b>	E.MC
<b>Manufacturer no.</b>	ELS 6/50-AS	<b>EAN</b>	4050571926588

Compact carriages, pistons 6mm,stroke 50mm, with stroke limitation for deploying (fixed stop)

## TECHNICAL DATA

Article authenticity	<b>Original product</b>
Condition of article	<b>New</b>
HS-Code	<b>84123100</b>
Weight	<b>18 kg</b>



## DESCRIPTION

Materials:

Body and plate: Anodized aluminium, piston rods: Stainless steel, Piston: Aluminium, Gaskets: NBR / PUR

Temperature range:

-10 to +60 °C

Operating pressure:

max. 7 bar

Piston speed

50 - 500 mm/s

Version:

With Magnetic piston

Optional:

with stroke limitation (fixed stop) while deploying (-10 mm) **-AS\***, with stroke limitation (fixed stop) retracting (-10 mm) **-AT\***, with stroke limitation (fixed stop) on both sides (-20 mm)-**A\***, with stroke limitation (shock absorber) while deploying (not Ø 6, Ø 8: -20mm, Ø 12: -18 mm, Ø 16 & 20: -25 mm,

Ø 25: -35 mm) **-BS\***, with stroke limitation (shock absorber) while retracting (not Ø 6, Ø 8: -20 mm, Ø 12: -18 mm, Ø 16 & 20: -25 mm, Ø 25: -35 mm) **-BT\***, with stroke limitation (shock absorber) on both sides (not Ø 6, Ø 8: -40 mm, Ø 12: -36 mm, Ø 16 & 20: -50 mm, Ø 25: -70 mm) **-B\***

Cylinder switch type:

D

Advantages:

- high rigidity,
- numerous fastening options,
- position holes for accurately repeatable workpiece mounting,
- stroke adjustable by stroke limiters (as fixed stop or shock absorber),
- main installation dimensions identical to SMC Series MXS

Piston diameter [mm]	6
Stroke [mm]	50
Stroke (adjustment range) [mm]	40 - 50
Version	with stroke limitation for deploying (fixed stop)
G (compressed air port)	M 5
Repair sets	<a href="#">ELS 6 REP</a>
A [mm]	30
B [mm]	30
BA [mm]	12
BB [mm]	5,5
BC [mm]	3,0
BD	M 2,5
BD1 [mm]	3,5
C [mm]	20
CA [mm]	17,5
F [mm]	38
FA [mm]	18
FB [mm]	11
FC (+0.03 / -0.2) [mm]	3 (2.5 deep)
FD [mm]	4
FE	M 3
FE1 [mm]	4,0
FF [mm]	38
H [mm]	24
HA [mm]	48
HB [mm]	41
HC [mm]	17
HE	M 4
HE1 [mm]	8
HF [mm]	3,3

KA [mm]	24
KB [mm]	10
KC	M 3
KC1 [mm]	5
L [mm]	10,5
LA [mm]	24,0
LB [mm]	16,0
LC [mm]	5,5
LD [mm]	12,5
LE [mm]	6,5
LF [mm]	3,0
LG [mm]	5,0
LH [mm]	7,0
LJ [mm]	2
LK [mm]	3,50
LM [mm]	3,0
LN [mm]	5,5
LO	M 2,5
LO1 [mm]	3,5
LP	M 2,5
LP1 [mm]	4,0
M [mm]	100
MA [mm]	5
N	6x
N1	4x
N2	4x
Z [mm]	99,5