

EMC ELS 8 BS. Stossdämpfer ausfahrend für Kompaktschlitten ELS

Item no. FL-ELS-8-BS

Manufacturer E.MC

EAN 4050571926793

Stossdämpfer ausfahrend für Kompaktschlitten ELS

TECHNICAL DATA

HS-Code 84819000

Weight 0.035 kg



DESCRIPTION

Materials:

Body and plate: Anodized aluminium, piston rods: Stainless steel, Piston: Aluminium, Gaskets: NBR / PUR

Temperature range:

-10 to +60 °C

Operating pressure:

max. 7 bar

Piston speed

50 - 500 mm/s

Version:

With Magnetic piston

Optional:

with stroke limitation (fixed stop) while deploying (-10 mm) **-AS***, with stroke limitation (fixed stop) retracting (-10 mm) **-AT***, with stroke limitation (fixed stop) on both sides (-20 mm) **-A***, with stroke limitation (shock absorber) while deploying (not Ø 6, Ø 8: -20mm, Ø 12: -18 mm, Ø 16 & 20: -25 mm, Ø 25: -35 mm) **-BS***, with stroke limitation (shock absorber) while retracting (not Ø 6, Ø 8: -20 mm,

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

Ø 12: -18 mm, Ø 16 & 20: -25 mm, Ø 25: -35 mm) **-BT***, with stroke limitation (shock absorber) on both sides (not Ø 6, Ø 8: -40 mm, Ø 12: -36 mm, Ø 16 & 20: -50 mm, Ø 25: -70 mm) **-B***

Cylinder switch type:

D

Advantages:

- high rigidity,
- numerous fastening options,
- position holes for accurately repeatable workpiece mounting,
- stroke adjustable by stroke limiters (as fixed stop or shock absorber),
- main installation dimensions identical to SMC Series MXS

Piston diameter [mm]	8
Version	Retrofit kit for shock absorber extending