

EMC EMQ 30 A. Compact swivel table, size 30, with fixed stop

Item no. FL-EMQ-30-A

Manufacturer E.MC

EAN 4050571931766

Compact swivel table, size 30, with fixed stop

TECHNICAL DATA

HS-Code **40169300**Weight **1.4 kg**

DESCRIPTION

Materials:

Body and swivel table anodized aluminum, Piston: Stainless steel with magnet insert, Pinion: Steel, Seals: NBR

Temperature range:

0 to +60 °C

Operating pressure:

max. 10 bar (size 7: max. 7 bar), with shock absorbers: max. 6 bar

Swivel angle:

adjustable 0° - 190°

Version:

With Magnetic piston

Cylinder switch type:

D

Advantages:

- Positioning hole on swivel table, body top and body at bottom for repeatable workpiece mounting,

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/3

- Internal table diameter and external table diameter as well as bottom hole suitable for precise alignment of the swivel axis,
- Simple fitting from below and above,
- Hollow shaft for media supply to devices mounted on the swivel table,
- Air connection either from the front or laterally (closed with sealing plugs),
- Main dimensions identical to SMC series MSQ / EMSQ

Version	with fixed stop
size	30
optimum swing time for 90° [s]	0,2 - 1,0
Operating pressure [bar]	max. 10
G (compressed air port)	G 1/8"
optional compressed air port (closed)	M 5
Repair sets	EMQ 30 REP
Spare shock absorber (1 count)	EMQ 20/30 SD
AA [mm]	72,4
A [mm]	70
AV [mm]	29,0
AW [mm]	18,5
AY [mm]	5
BA	12,0
BB [mm]	50,0
BC [mm]	32,5
BD [mm]	84
BE [mm]	37
CA [mm]	7,0
CB [mm]	33,5
D (h9) [mm]	65
DD (h9) [mm]	67
DE (H9)	32
DF [mm]	10
DG (H9)	22
FA [mm]	9,8
FB [mm]	5,0
FC [mm]	3,5
FD [mm]	6,5
H [mm]	17

J [mm]	8,6
JA [mm]	14
JB	8,5
JC	M 10
JC1 [mm]	15
JJ	M 6
JU	M 10x1 (FT)
Q [mm]	40
S [mm]	127
SD [mm]	11,5
SE [mm]	14
SF [mm]	65
SU [mm]	24,8
UU [mm]	57
WA [mm]	23,0
WB [mm]	4H9 (4.5 deep)
WD	M 6
WD1 [mm]	10
WF	48
XA	39
YA [mm]	28