

EMC EU 10/10. Direct assembly cylinder, Piston 10mm, stroke 10mm, Standard

Item no. FL-EU-10/10

Manufacturer E.MC

EAN 4050571871772

Direct assembly cylinder, Piston 10mm,stroke 10mm, Standard

TECHNICAL DATA

HS-Code 84123100

Weight 0.05 kg



DESCRIPTION

Materials:

Body: Anodized aluminium, piston rod: Stainless steel, Piston: Aluminium, Gaskets: NBR / PUR

Temperature range:

-10 to +60 °C

Operating pressure:

max. 7 bar

Version:

with magnetic piston, piston diameter 6 mm and 10 mm are supplied with two nuts on piston rod

Cylinder switch type:

D

Advantages:

- space saving through square housing, which allows a direct mounting without mounting material
- can be fastened on each of the 6 sides of the square,
- main mounting dimensions identical to SMC series CDU / CDUK

Piston diameter [mm]

10

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

Stroke [mm]	10
Version	Standard
E (piston rod thread)	M 4
G (compressed air port)	M 5
Repair sets	EU 10 REP
A1 [mm]	36
A2 [mm]	52
B [mm]	15
C [mm]	24
D [mm]	4
D1 [mm]	16
E1 [mm]	10,0
E2 [mm]	11,0
G1 [mm]	15,5
G2 [mm]	10,0
H [mm]	5.8 (4.5 deep)
H1 [mm]	3,2
H2 [mm]	11
H3 [mm]	7
H4 [mm]	9
J	M 3
J1 [mm]	18
J2 [mm]	5