

EMC EU 32/5. Direct assembly cylinder, Piston 32mm, stroke 5mm, Standard

Item no. FL-EU-32/5

Manufacturer E.MC

EAN 4050571872151

Direct assembly cylinder, Piston 32mm,stroke 5mm, Standard

TECHNICAL DATA

HS-Code 84123100

Weight 0.4 kg



DESCRIPTION

Materials:

Body: Anodized aluminium, piston rod: Stainless steel, Piston: Aluminium, Gaskets: NBR / PUR

Temperature range:

-10 to +60 °C

Operating pressure:

max. 7 bar

Version:

with magnetic piston, piston diameter 6 mm and 10 mm are supplied with two nuts on piston rod

Cylinder switch type:

D

Advantages:

- space saving through square housing, which allows a direct mounting without mounting material
- can be fastened on each of the 6 sides of the square,
- main mounting dimensions identical to SMC series CDU / CDUK

Piston diameter [mm]

32

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

Stroke [mm]	5
Version	Standard
E (piston rod thread)	M 10x1,25
G (compressed air port)	G 1/8"
Repair sets	EU 32 REP
A1 [mm]	52
A2 [mm]	79
B [mm]	40
C [mm]	62
D [mm]	12
D1 [mm]	27
E1 [mm]	19,5
E2 [mm]	22,0
G1 [mm]	23,0
G2 [mm]	12,5
G3 [mm]	4,5
G4 [mm]	9,0
H [mm]	11.0 (11.5 deep)
H1 [mm]	6,6
H2 [mm]	24
H3 [mm]	11
H4 [mm]	24
J	M 6
J1 [mm]	48
J2 [mm]	9
SW [mm]	10