

EMC EUK 10/5. Direct assembly cylinder, Piston 10mm, stroke 5mm, non-rotating piston rod

Item no. FL-EUK-10/5

Manufacturer E.MC

EAN 4050571872311

Direct assembly cylinder, Piston 10mm,stroke 5mm, non-rotating piston rod

TECHNICAL DATA

HS-Code **84123100**

Weight **0.05 kg**



DESCRIPTION

Materials:

Body: Anodized aluminium, piston rod: Stainless steel, Piston: Aluminium, Gaskets: NBR / PUR

Temperature range:

-10 to +60 °C

Operating pressure:

max. 7 bar

Version:

with magnetic piston, piston diameter 6 mm and 10 mm are supplied with two nuts on piston rod

Cylinder switch type:

D

Advantages:

- space saving through square housing, which allows a direct mounting without mounting material
- can be fastened on each of the 6 sides of the square,
- main mounting dimensions identical to SMC series CDU / CDUK

Piston diameter [mm]

10

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

Stroke [mm]	5
Version	non-rotating piston rod
E (piston rod thread)	M 4
G (compressed air port)	M 5
Repair sets	EU 10 REP
A1 [mm]	36
A3 [mm]	57
B [mm]	15
C [mm]	24
D [mm]	4
D2 [mm]	21
E1 [mm]	10,0
E2 [mm]	11,0
G1 [mm]	15,5
G2 [mm]	10,0
H [mm]	5.8 (4.5 deep)
H1 [mm]	3,2
H2 [mm]	11
H3 [mm]	7
H4 [mm]	9
J	M 3
J1 [mm]	18
J2 [mm]	5
K [mm]	8
K1 [mm]	12
K2 [mm]	13
K3 [mm]	20,4
K4 [mm]	11,8