

EMC EUK 20/20. Direct assembly cylinder, Piston 20mm, stroke 20mm, non-rotating piston rod

Item no. FL-EUK-20/20

Manufacturer E.MC

EAN 4050571872427

Direct assembly cylinder, Piston 20mm,stroke 20mm, non-rotating piston rod

TECHNICAL DATA

HS-Code **84123100**

Weight **0.195 kg**



DESCRIPTION

Materials:

Body: Anodized aluminium, piston rod: Stainless steel, Piston: Aluminium, Gaskets: NBR / PUR

Temperature range:

-10 to +60 °C

Operating pressure:

max. 7 bar

Version:

with magnetic piston, piston diameter 6 mm and 10 mm are supplied with two nuts on piston rod

Cylinder switch type:

D

Advantages:

- space saving through square housing, which allows a direct mounting without mounting material
- can be fastened on each of the 6 sides of the square,
- main mounting dimensions identical to SMC series CDU / CDUK

Piston diameter [mm]

20

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

Stroke [mm]	20
Version	non-rotating piston rod
E (piston rod thread)	M 6
G (compressed air port)	M 5
Repair sets	EU 20 REP
A1 [mm]	46
A3 [mm]	75
B [mm]	26
C [mm]	40
D [mm]	8
D2 [mm]	29
E1 [mm]	12,0
E2 [mm]	14,0
G1 [mm]	21,0
G2 [mm]	10,0
G3 [mm]	4,5
G4 [mm]	5,5
H [mm]	9.5 (8.0 deep)
H1 [mm]	5,5
H2 [mm]	16
H3 [mm]	9
H4 [mm]	16
J	M 5
J1 [mm]	30
J2 [mm]	8
K [mm]	8
K1 [mm]	20
K2 [mm]	16
K3 [mm]	32,0
K4 [mm]	19,8
SW [mm]	6