

# EMC EUK 25/20. Direct assembly cylinder, Piston 25mm, stroke 20mm, non-rotating piston rod

<b>Item no.</b>	FL-EUK-25/20	<b>Manufacturer</b>	E.MC
<b>Manufacturer no.</b>	EUK 25/20	<b>EAN</b>	4050571872502

Direct assembly cylinder, Piston 25mm,stroke 20mm, non-rotating piston rod

## TECHNICAL DATA

Article authenticity	<b>Original product</b>
Condition of article	<b>New</b>
HS-Code	<b>84123100</b>
Weight	<b>33 kg</b>



## DESCRIPTION

Materials:

Body: Anodized aluminium, piston rod: Stainless steel, Piston: Aluminium, Gaskets: NBR / PUR

Temperature range:

-10 to +60 °C

Operating pressure:

max. 7 bar

Version:

with magnetic piston, piston diameter 6 mm and 10 mm are supplied with two nuts on piston rod

Cylinder switch type:

D

Advantages:

- space saving through square housing, which allows a direct mounting without mounting material
- can be fastened on each of the 6 sides of the square,
- main mounting dimensions identical to SMC series CDU / CDUK

Piston diameter [mm]	25
Stroke [mm]	20
Version	non-rotating piston rod
E (piston rod thread)	M 8
G (compressed air port)	M 5
Repair sets	<a href="#">EU 25 REP</a>
A1 [mm]	50
A3 [mm]	83
B [mm]	32
C [mm]	50
D [mm]	10
D2 [mm]	33
E1 [mm]	15,5
E2 [mm]	18,0
G1 [mm]	23,0
G2 [mm]	10,0
G3 [mm]	4,5
G4 [mm]	6,0
H [mm]	9.5 (9.0 deep)
H1 [mm]	5,5
H2 [mm]	20
H3 [mm]	10
H4 [mm]	20
J	M 5
J1 [mm]	38
J2 [mm]	8
K [mm]	10
K1 [mm]	22
K2 [mm]	19
K3 [mm]	40,0
K4 [mm]	24,8
SW [mm]	8