

EMC EXH 10/40. Compact carriage, piston 10mm, stroke 40mm

Item no. FL-EXH-10/40

Manufacturer E.MC

EAN 4050571871314

Compact carriage, piston 10mm,stroke 40mm

TECHNICAL DATA

HS-Code 84123100

Weight 0.2 kg



DESCRIPTION

Materials:

Body and plate: Anodized aluminium, piston rod: Steel, hard chrome-plated, piston: Aluminium,
Gaskets: NBR / PUR

Temperature range:

-10 to +70 °C

Operating pressure:

max. 7 bar

Permitted kinetic energy:

Ø 6: 12.5 mJ, Ø 10: 25 mJ, Ø 16: 50 mJ, Ø 20: 100mJ

Version:

With Magnetic piston

Cylinder switch type:

D

Advantages:

•high stiffness,

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/3

- compressed air connection possible from three sides,
- numerous mounting options,
- main mounting dimensions identical to SMC series MXH

Piston diameter [mm]	10
Stroke [mm]	40
Version	Compact sled
P (compressed air port)	M 5
Repair sets	EXH 10 REP
A [mm]	5
B [mm]	12
C [mm]	13
D [mm]	11,5
E [mm]	5
F [mm]	35,0
G [mm]	46,5
H [mm]	7,5
I [mm]	5,0
J [mm]	6x
K [mm]	23
L [mm]	6,5
LA [mm]	20
LB [mm]	20
LT [mm]	79
M [mm]	20
N [mm]	38,0
NS [mm]	45
O [mm]	8,0
P1	M 4
P2	M 4
P3	M 4
P4	M 5
P5 [mm]	7.5 (4.4 deep)
P6 [mm]	4,3
Q1 [mm]	20
Q2 [mm]	47,0

R1 [mm]	11
R2 [mm]	18
S [mm]	46,0
S1 [mm]	6
S2 [mm]	7,5
S3 [mm]	8,0
T [mm]	21,5
U [mm]	13,0
V [mm]	5,0
W [mm]	23
X [mm]	11
Y [mm]	19
Z [mm]	11