

EMC SES 25/25-B. Compact cylinders, double acting, piston 25 mm, stroke 25 mm

Item no. FL-SES-25/25-B

Manufacturer E.MC

EAN 4050571618612

Compact cylinders, double acting, piston 25 mm, stroke 25 mm

TECHNICAL DATA

HS-Code 84123100

Weight 0.29 kg



DESCRIPTION

Materials:

Head and foot: painted aluminium, cylinder tube: anodized aluminium, piston rod: hard chromium plated steel, seal: NBR

Temperature range:

-20 to +60 °C

Operating pressure:

max. 10 bar

Version:

With Magnetic piston

Cylinder switch type:

F

Optional:

Piston rod with male thread **-B**

Piston diameter [mm]	25
----------------------	----

Stroke [mm]	25
-------------	----

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

Version	Piston rod with male thread
S (piston rod male thread)	M 10x1,25
G (compressed air port)	M 5
A [mm]	45,0
B [mm]	39,5
C [mm]	12
D [mm]	10
E [mm]	40
F [mm]	7
J [mm]	41,5
K [mm]	8
L [mm]	5,5
M [mm]	26
N	M 5
O [mm]	6
Q [mm]	22
R [mm]	20