

EMC SES 40/80. Compact cylinders, double acting, piston 40 mm, stroke 80 mm

Item no. FL-SES-40/80

Manufacturer E.MC

EAN 4050571619282

Compact cylinders, double acting, piston 40 mm, stroke 80 mm

TECHNICAL DATA

HS-Code **84123100**

Weight **0.9 kg**



DESCRIPTION

Materials:

Head and foot: painted aluminium, cylinder tube: anodized aluminium, piston rod: hard chromium plated steel, seal: NBR

Temperature range:

-20 to +60 °C

Operating pressure:

max. 10 bar

Version:

With Magnetic piston

Cylinder switch type:

F

Optional:

Piston rod with male thread **-B**

Piston diameter [mm]	40
----------------------	----

Stroke [mm]	80
-------------	----

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

Version	Standard
H (piston rod female thread)	M 6
G (compressed air port)	G 1/8"
A [mm]	52,0
B [mm]	45,5
C [mm]	14
D [mm]	12
E [mm]	60
F [mm]	8
J [mm]	62,5
K [mm]	10
L [mm]	6,5
M [mm]	42
N	M 6
O [mm]	6