

EMC SES 63/100. Compact cylinders, double acting, piston 63 mm, stroke 100 mm

Item no. FL-SES-63/100

Manufacturer E.MC

EAN 4050571619626

Compact cylinders, double acting, piston 63 mm, stroke 100 mm

TECHNICAL DATA

HS-Code **84123100**

Weight **2.1 kg**



DESCRIPTION

Materials:

Head and foot: painted aluminium, cylinder tube: anodized aluminium, piston rod: hard chromium plated steel, seal: NBR

Temperature range:

-20 to +60 °C

Operating pressure:

max. 10 bar

Version:

With Magnetic piston

Cylinder switch type:

F

Optional:

Piston rod with male thread **-B**

Piston diameter [mm] 63

Stroke [mm] 100

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

Version	Standard
H (piston rod female thread)	M 8
G (compressed air port)	G 1/8"
Repair sets	SES 63 REP
A [mm]	57,5
B [mm]	50,0
C [mm]	16
D [mm]	16
E [mm]	87
F [mm]	8
J [mm]	91,0
K [mm]	13
L [mm]	7,5
M [mm]	62
N	M 10
O [mm]	8