

EMC SFS 100/60-B. ISO 21287 cylinders, double acting, piston 100 mm, stroke 60 mm

Item no. FL-SFS-100/60-B

Manufacturer E.MC

EAN 4050571927325

ISO 21287 cylinders, double acting, piston 100 mm, stroke 60 mm

TECHNICAL DATA

HS-Code **84123100**Norm **ISO 21287**Weight **3.3 kg**

STANDARDS & COMPLIANCE

ISO 21287

DESCRIPTION

Materials:

Head and foot: aluminium, cylinder tube: anodized aluminium, piston rod: stainless steel (Ø 32 - 100: hard chromium plated steel), seal: NBR / PUR

Temperature range:

-20 to +80 °C

Operating pressure:

max. 10 bar

Version:

With Magnetic piston

Cylinder switch type:

D, A

Optional:

Piston rod with male thread **-B****esd.equipment**

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

Piston diameter [mm]	100
Stroke [mm]	60
Version	Piston rod with male thread
KK (piston rod male thread)	M 16x1,5
G (compressed air port)	G 1/8"
Repair sets	SFS 100 REP
A [mm]	28
AD [mm]	32
AF [mm]	21
BG [mm]	25
CH [mm]	27
E [mm]	109,0
E1 [mm]	4,5
LA [mm]	5
PL1 [mm]	24,5
PL2 [mm]	19,0
RT	M 10
S [mm]	14
TG [mm]	89,0
WH [mm]	10
ZA [mm]	67
ZB [mm]	77