

EMC SFS 20/15. ISO 21287 cylinders, double acting, piston 20 mm, stroke 15 mm

Item no. FL-SFS-20/15

Manufacturer E.MC

EAN 4050571927424

ISO 21287 cylinders, double acting, piston 20 mm, stroke 15 mm

TECHNICAL DATA

HS-Code 84123100

Weight 0.165 kg



STANDARDS & COMPLIANCE

ISO 21287

DESCRIPTION

Materials:

Head and foot: aluminium, cylinder tube: anodized aluminium, piston rod: stainless steel (Ø 32 - 100: hard chromium plated steel), seal: NBR / PUR

Temperature range:

-20 to +80 °C

Operating pressure:

max. 10 bar

Version:

With Magnetic piston

Cylinder switch type:

D, A

Optional:

Piston rod with male thread **-B****esd.equipment**

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

Piston diameter [mm]	20
Stroke [mm]	15
Version	Standard
KF (piston rod female thread)	M 6
G (compressed air port)	M 5
Repair sets	SFS 20 REP
AD [mm]	10
AF [mm]	10
BG [mm]	15
CH [mm]	8
E [mm]	36,0
E1 [mm]	0
LA [mm]	5
PL1 [mm]	15,5
PL2 [mm]	5,5
RT	M 5
S [mm]	3
TG [mm]	22,0
WH [mm]	6
ZA [mm]	37
ZB [mm]	43