

## EMC SFS 25/20. ISO 21287 cylinders, double acting, piston 25 mm, stroke 20 mm

Item no. FL-SFS-25/20

Manufacturer E.MC

EAN 4050571927738

ISO 21287 cylinders, double acting, piston 25 mm, stroke 20 mm

### TECHNICAL DATA

HS-Code **84123100**Norm **ISO 21287**Weight **0.22 kg**

### STANDARDS & COMPLIANCE

**ISO 21287**

### DESCRIPTION

Materials:

Head and foot: aluminium, cylinder tube: anodized aluminium, piston rod: stainless steel (Ø 32 - 100: hard chromium plated steel), seal: NBR / PUR

Temperature range:

-20 to +80 °C

Operating pressure:

max. 10 bar

Version:

With Magnetic piston

Cylinder switch type:

D, A

Optional:

Piston rod with male thread **-B****esd.equipment**

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

**esd.equipment**

Page 1/2

|                               |                            |
|-------------------------------|----------------------------|
| Piston diameter [mm]          | 25                         |
| Stroke [mm]                   | 20                         |
| Version                       | Standard                   |
| KF (piston rod female thread) | M 6                        |
| G (compressed air port)       | M 5                        |
| Repair sets                   | <a href="#">SFS 25 REP</a> |
| AD [mm]                       | 12                         |
| AF [mm]                       | 10                         |
| BG [mm]                       | 15                         |
| CH [mm]                       | 10                         |
| E [mm]                        | 40,0                       |
| E1 [mm]                       | 0                          |
| LA [mm]                       | 5                          |
| PL1 [mm]                      | 17,5                       |
| PL2 [mm]                      | 5,5                        |
| RT                            | M 5                        |
| S [mm]                        | 0                          |
| TG [mm]                       | 26,0                       |
| WH [mm]                       | 6                          |
| ZA [mm]                       | 39                         |
| ZB [mm]                       | 45                         |