

## EMC SFS 32/60. ISO 21287 cylinders, double acting, piston 32 mm, stroke 60 mm

Item no. FL-SFS-32/60

Manufacturer E.MC

EAN 4050571928148

ISO 21287 cylinders, double acting, piston 32 mm, stroke 60 mm

### TECHNICAL DATA

HS-Code 84123100

Norm ISO 21287

Weight 0.5 kg



### STANDARDS & COMPLIANCE

ISO 21287

### DESCRIPTION

Materials:

Head and foot: aluminium, cylinder tube: anodized aluminium, piston rod: stainless steel (Ø 32 - 100: hard chromium plated steel), seal: NBR / PUR

Temperature range:

-20 to +80 °C

Operating pressure:

max. 10 bar

Version:

With Magnetic piston

Cylinder switch type:

D, A

Optional:

Piston rod with male thread **-B****esd.equipment**

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

**esd.equipment**

Page 1/2

|                               |                            |
|-------------------------------|----------------------------|
| Piston diameter [mm]          | 32                         |
| Stroke [mm]                   | 60                         |
| Version                       | Standard                   |
| KF (piston rod female thread) | M 8                        |
| G (compressed air port)       | G 1/8"                     |
| Repair sets                   | <a href="#">SFS 32 REP</a> |
| AD [mm]                       | 16                         |
| AF [mm]                       | 12                         |
| BG [mm]                       | 16                         |
| CH [mm]                       | 14                         |
| E [mm]                        | 45,5                       |
| E1 [mm]                       | 2,5                        |
| LA [mm]                       | 5                          |
| PL1 [mm]                      | 15,5                       |
| PL2 [mm]                      | 8,0                        |
| RT                            | M 6                        |
| S [mm]                        | 0                          |
| TG [mm]                       | 32,5                       |
| WH [mm]                       | 7                          |
| ZA [mm]                       | 44                         |
| ZB [mm]                       | 51                         |