

## EMC SFS 40/50-B. ISO 21287 cylinders, double acting, piston 40 mm, stroke 50 mm

Item no. FL-SFS-40/50-B

Manufacturer E.MC

EAN 4050571928414

ISO 21287 cylinders, double acting, piston 40 mm, stroke 50 mm

### TECHNICAL DATA

HS-Code 84123100

Weight 0.6 kg



### STANDARDS & COMPLIANCE

ISO 21287

### DESCRIPTION

Materials:

Head and foot: aluminium, cylinder tube: anodized aluminium, piston rod: stainless steel (Ø 32 - 100: hard chromium plated steel), seal: NBR / PUR

Temperature range:

-20 to +80 °C

Operating pressure:

max. 10 bar

Version:

With Magnetic piston

Cylinder switch type:

D, A

Optional:

Piston rod with male thread **-B****esd.equipment**

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

**esd.equipment**

Page 1/2

|                             |                             |
|-----------------------------|-----------------------------|
| Piston diameter [mm]        | 40                          |
| Stroke [mm]                 | 50                          |
| Version                     | Piston rod with male thread |
| KK (piston rod male thread) | M 10x1,25                   |
| G (compressed air port)     | G 1/8"                      |
| Repair sets                 | <a href="#">SFS 40 REP</a>  |
| A [mm]                      | 19                          |
| AD [mm]                     | 16                          |
| AF [mm]                     | 12                          |
| BG [mm]                     | 16                          |
| CH [mm]                     | 14                          |
| E [mm]                      | 53,0                        |
| E1 [mm]                     | 2,5                         |
| LA [mm]                     | 5                           |
| PL1 [mm]                    | 16,5                        |
| PL2 [mm]                    | 9,5                         |
| RT                          | M 6                         |
| S [mm]                      | 0                           |
| TG [mm]                     | 38,0                        |
| WH [mm]                     | 7                           |
| ZA [mm]                     | 45                          |
| ZB [mm]                     | 52                          |