

EMC SFS 50/200. ISO 21287 cylinders, double acting, piston 50 mm, stroke 200 mm

Item no. FL-SFS-50/200

Manufacturer E.MC

EAN 4050571928599

ISO 21287 cylinders, double acting, piston 50 mm, stroke 200 mm

TECHNICAL DATA

HS-Code **84123100**Weight **1.9 kg**

STANDARDS & COMPLIANCE

ISO 21287

DESCRIPTION

Materials:

Head and foot: aluminium, cylinder tube: anodized aluminium, piston rod: stainless steel (Ø 32 - 100: hard chromium plated steel), seal: NBR / PUR

Temperature range:

-20 to +80 °C

Operating pressure:

max. 10 bar

Version:

With Magnetic piston

Cylinder switch type:

D, A

Optional:

Piston rod with male thread **-B****esd.equipment**

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

Piston diameter [mm]	50
Stroke [mm]	200
Version	Standard
KF (piston rod female thread)	M 10
G (compressed air port)	G 1/8"
Repair sets	SFS 50 REP
AD [mm]	20
AF [mm]	16
BG [mm]	20
CH [mm]	17
E [mm]	63,0
E1 [mm]	2,5
LA [mm]	5
PL1 [mm]	16,0
PL2 [mm]	10,5
RT	M 8
S [mm]	4
TG [mm]	46,5
WH [mm]	8
ZA [mm]	45
ZB [mm]	53