

EMC SFS 80/30-B. ISO 21287 cylinders, double acting, piston 80 mm, stroke 30 mm

Item no.	FL-SFS-80/30-B	Manufacturer	E.MC
Manufacturer no.	SFS 80/30-B	EAN	4050571929237

ISO 21287 cylinders, double acting, piston 80 mm, stroke 30 mm

TECHNICAL DATA

Article authenticity	Original product
Condition of article	New
HS-Code	84123100
Weight	15 kg



STANDARDS & COMPLIANCE

ISO 21287

DESCRIPTION

Materials:

Head and foot: aluminium, cylinder tube: anodized aluminium, piston rod: stainless steel (Ø 32 - 100: hard chromium plated steel), seal: NBR / PUR

Temperature range:

-20 to +80 °C

Operating pressure:

max. 10 bar

Version:

With Magnetic piston

Cylinder switch type:

D, A

Optional:

Piston rod with male thread -B

Piston diameter [mm]	80
Stroke [mm]	30
Version	Piston rod with male thread
KK (piston rod male thread)	M 16x1,5
G (compressed air port)	G 1/8"
Repair sets	SFS 80 REP
A [mm]	28
AD [mm]	25
AF [mm]	21
BG [mm]	25
CH [mm]	22
E [mm]	92,0
E1 [mm]	3,5
LA [mm]	5
PL1 [mm]	17,0
PL2 [mm]	15,0
RT	M 10
S [mm]	10
TG [mm]	72,0
WH [mm]	10
ZA [mm]	54
ZB [mm]	64