

## EMC SFSA 20/40. ISO 21287 cylinders, double acting, piston 20 mm, stroke 40 mm

Item no. FL-SFSA-20/40

Manufacturer E.MC

EAN 4050571931865

ISO 21287 cylinders, double acting, piston 20 mm, stroke 40 mm

### TECHNICAL DATA

HS-Code **84123100**Norm **ISO 21287**Weight **0.28 kg**

### STANDARDS & COMPLIANCE

**ISO 21287**

### DESCRIPTION

Materials:

Head and foot: aluminium, cylinder tube: anodized aluminium, piston rod: stainless steel (Ø 32 - 100: hard chromium plated steel), seal: NBR / PUR

Temperature range:

-20 to +80 °C

Operating pressure:

max. 10 bar

Version:

With Magnetic piston

Cylinder switch type:

D, A

Optional:

Piston rod with male thread **-B****esd.equipment**

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

**esd.equipment**

Page 1/2

|                         |                            |
|-------------------------|----------------------------|
| Piston diameter [mm]    | 20                         |
| Stroke [mm]             | 40                         |
| Version                 | non-rotating piston rod    |
| G (compressed air port) | M 5                        |
| Repair sets             | <a href="#">SFS 20 REP</a> |
| AD [mm]                 | 10                         |
| AF [mm]                 | 8                          |
| BG [mm]                 | 15                         |
| D1 [mm]                 | 17                         |
| D2                      | M 4                        |
| D3 [mm]                 | 4                          |
| E [mm]                  | 36,0                       |
| KJ [mm]                 | 35,0                       |
| LA [mm]                 | 5                          |
| PL1 [mm]                | 15,5                       |
| PL2 [mm]                | 5,5                        |
| RS [mm]                 | 4,2                        |
| RT                      | M 5                        |
| RU [mm]                 | 7,3                        |
| S [mm]                  | 3                          |
| TG [mm]                 | 22,0                       |
| ZA [mm]                 | 37                         |
| ZD [mm]                 | 51,0                       |