

EMC SFSA 40/60. ISO 21287 cylinders, double acting, piston 40 mm, stroke 60 mm

Item no. FL-SFSA-40/60

Manufacturer E.MC

EAN 4050571932190

ISO 21287 cylinders, double acting, piston 40 mm, stroke 60 mm

TECHNICAL DATA

HS-Code 84123100

Norm ISO 21287

Weight 0.75 kg



STANDARDS & COMPLIANCE

ISO 21287

DESCRIPTION

Materials:

Head and foot: aluminium, cylinder tube: anodized aluminium, piston rod: stainless steel (Ø 32 - 100: hard chromium plated steel), seal: NBR / PUR

Temperature range:

-20 to +80 °C

Operating pressure:

max. 10 bar

Version:

With Magnetic piston

Cylinder switch type:

D, A

Optional:

Piston rod with male thread **-B****esd.equipment**

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

Piston diameter [mm]	40
Stroke [mm]	60
Version	non-rotating piston rod
G (compressed air port)	G 1/8"
Repair sets	SFS 40 REP
AD [mm]	16
AF [mm]	10
BG [mm]	16
D1 [mm]	33
D2	M 5
D3 [mm]	5
E [mm]	53,0
KJ [mm]	52,0
LA [mm]	5
PL1 [mm]	16,5
PL2 [mm]	9,5
RS [mm]	5,2
RT	M 6
RU [mm]	9,0
S [mm]	0
TG [mm]	38,0
ZA [mm]	45
ZD [mm]	62,5