

EMC SFSBS 40/5. ISO 21287 cylinders, single acting, piston 40 mm, stroke 5 mm

Item no. FL-SFSBS-40/5 **Manufacturer** E.MC
Manufacturer no. SFSBS 40/5 **EAN** 4050571929718

ISO 21287 cylinders, single acting, piston 40 mm, stroke 5 mm

TECHNICAL DATA

Article authenticity	Original product
Condition of article	New
HS-Code	84123100
Weight	34 kg



STANDARDS & COMPLIANCE

ISO 21287

DESCRIPTION

Materials:

Head and foot: aluminium, cylinder tube: anodized aluminium, piston rod: stainless steel (Ø 32 - 63: hard chromium-plated steel) seal: NBR / PUR

Temperature range:

-20 to +80 °C

Operating pressure:

max. 10 bar

Version:

With Magnetic piston

Cylinder switch type:

D, A

Optional:

Piston rod with male thread **-B**

Piston diameter [mm]	40
Stroke [mm]	5
Version	Standard
KF (piston rod female thread)	M 8
G (compressed air port)	G 1/8"
Repair sets	SFS 40 REP
AD [mm]	16
AF [mm]	12
BG [mm]	16
CH [mm]	14
E [mm]	53,0
E1 [mm]	2,5
LA [mm]	5
PL1 [mm]	16,5
PL2 [mm]	9,5
RT	M 6
S [mm]	0
TG [mm]	38,0
WH [mm]	7
ZA [mm]	45
ZB [mm]	52