

EMC SQKL 20/30. Swivel clamps / clamping cylinder 20 mm, clamping stroke 30mm left turning (turns counter-clockwis

Item no. FL-SQKL-20/30

Manufacturer E.MC

EAN 4050571930066

Swivel clamps / clamping cylinder Ø 20 mm, clamping stroke 30mm left turning (turns counter-clockwis

TECHNICAL DATA

HS-Code	84123100
Weight	0.42 kg



DESCRIPTION

Materials:

Body: Aluminium anodised, piston rod: hard chromium plated steel, seals: NBR / PUR

Temperature range:

-10 to +70 °C

Operating pressure:

max. 10 bar

Swivel angle:

90° (± 10°)

Version:

With Magnetic piston

Note:

- only operate cylinders positioned vertically or suspended
- clamps only allowed inside the clamping stroke and on level surfaces,
- workpiece must be idle during clamping process

Advantages:

esd.equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com

esd.equipment

Page 1/2

- simple mechanics, robust construction
- supplied with removable lever arm, which can be adjusted in 90° increments
- Main dimensions identical to SMC Series MKB

Cylinder switch type:

D

Version	left turning* (turns counter-clockwise at terminals)
Piston diameter [mm]	20
Clamping stroke [mm]	30
Rotary lift [mm]	9,5
effective piston diameter when clamping [mm]	16,0
G (compressed air port)	M 5
Repair sets	SOK 20 REP
A [mm]	36
B [mm]	4,0
C [mm]	25,5
D [mm]	10
E [mm]	10 - 21
F [mm]	9,5
H [mm]	12
I [mm]	7
M (retracted) [mm]	52,0
M (extended) [mm]	91,5
N [mm]	14
O [mm]	51
P [mm]	35
Q [mm]	26,0
R [mm]	62,0
S [mm]	15,5
U	16
V	M 6
Y (+0/-0,05) [mm]	18
Z	M 6