

EMC SQKL 25/20. Swivel clamps / clamping cylinder 25 mm, clamping stroke 20mm left turning (turns counter-clockwis

Item no. FL-SQKL-25/20

Manufacturer E.MC

EAN 4050571930080

Swivel clamps / clamping cylinder Ø 25 mm, clamping stroke 20mm left turning (turns counter-clockwis

TECHNICAL DATA

HS-Code	84123100
Weight	0.44 kg



DESCRIPTION

Materials:

Body: Aluminium anodised, piston rod: hard chromium plated steel, seals: NBR / PUR

Temperature range:

-10 to +70 °C

Operating pressure:

max. 10 bar

Swivel angle:

90° (± 10°)

Version:

With Magnetic piston

Note:

- only operate cylinders positioned vertically or suspended
- clamps only allowed inside the clamping stroke and on level surfaces,
- workpiece must be idle during clamping process

Advantages:

esd.equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com

esd.equipment

Page 1/2

- simple mechanics, robust construction
- supplied with removable lever arm, which can be adjusted in 90° increments
- Main dimensions identical to SMC Series MKB

Cylinder switch type:

D

Version	left turning* (turns counter-clockwise at terminals)
Piston diameter [mm]	25
Clamping stroke [mm]	20
Rotary lift [mm]	9,5
effective piston diameter when clamping [mm]	21,9
G (compressed air port)	M 5
Repair sets	SOK 25 REP
A [mm]	40
B [mm]	4,0
C [mm]	28,0
D [mm]	10
E [mm]	10 - 21
F [mm]	10,0
H [mm]	12
I [mm]	7
M (retracted) [mm]	42,0
M (extended) [mm]	71,5
N [mm]	14
O [mm]	51
P [mm]	35
Q [mm]	27,5
R [mm]	63,0
S [mm]	15,5
U	16
V	M 6
Y (+0/-0,05) [mm]	23
Z	M 6