

EMC SQN 100/70 SZ. Compact cylinders, double acting, piston 100 mm, stroke 70 mm

Item no. FL-SQN-100/70-SZ

Manufacturer E.MC

EAN 4050571638436

Compact cylinders, double acting, piston 100 mm, stroke 70 mm

TECHNICAL DATA

HS-Code **84123100**

Weight **3.5 kg**



DESCRIPTION

Materials:

Body: anodized aluminium, piston rod: hard chromium plated steel, seal: NBR

Temperature range:

-10 to +60 °C

Operating pressure:

max. 10 bar

Version:

With Magnetic piston

Cylinder switch type:

D

Advantages:

- outstanding value,
- cylinder switches can be mounted on different sides,
- main mounting dimensions identical to SMC Series CQ2A (CQ2)

Piston diameter [mm]

100

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

Stroke [mm]	70
H (piston rod thread)	M 20
G (compressed air port)	G 3/8"
Repair sets	SQN 100 REP
A [mm]	75,0
B [mm]	63,0
C [mm]	27
D [mm]	30
E [mm]	117
F [mm]	13,0
J [mm]	6,5
K [mm]	27
L [mm]	12,0
M [mm]	94
N [mm]	11,0
O [mm]	17 (11 deep)
P	M 12
P1 [mm]	35,5
Q [mm]	23,0