

EMC XLE 100/250. ISO 15552 cylinders, piston 100 mm, stroke 250 mm, ECO

Item no.	FL-XLE-100/250	Manufacturer	E.MC
Manufacturer no.	XLE 100/250	EAN	4050571800512

ISO 15552 cylinders, piston 100 mm, stroke 250 mm, ECO

TECHNICAL DATA

Article authenticity	Original product
Condition of article	New
HS-Code	84123100
Weight	6 kg



STANDARDS & COMPLIANCE

ISO 15552

DESCRIPTION

Materials:

Head and base: Anodized aluminium, cylinder tube: Anodized aluminium section tube, Piston rod: Steel, hard chrome-plated, piston: Aluminium, Gasket: NBR / PUR

Temperature range:

-20 to +80 °C

Operating pressure:

max. 10 bar

Version:

with magnetic pistons and adjustable end position damping

Cylinder switch type:

D, A, Ø 125 and larger: C in combination with fastening C1 or C in combination with fastening C2

Piston diameter [mm]	100
Stroke [mm]	250
A (piston rod thread)	M 20x1,5

G (compressed air port) G 1/2"

Repair sets [XLE 100 REP](#)

B [mm]	25
C [mm]	55
D [mm]	36
F [mm]	40
G [mm]	51
H [mm]	189
K [mm]	4,0
M [mm]	110,0
N [mm]	89,0
CH [mm]	22
RT	M 10