

EMC XLE 32/40. ISO 15552 cylinders, piston 32 mm, stroke 40 mm, ECO

Item no. FL-XLE-32/40

Manufacturer E.MC

EAN 4050571800819

ISO 15552 cylinders, piston 32 mm, stroke 40 mm, ECO

TECHNICAL DATA

HS-Code 84123100

Norm ISO 15552

Weight 0.7 kg



STANDARDS & COMPLIANCE

ISO 15552

DESCRIPTION

Materials:

Head and base: Anodized aluminium, cylinder tube: Anodized aluminium section tube, Piston rod: Steel, hard chrome-plated, piston: Aluminium, Gasket: NBR / PUR

Temperature range:

-20 to +80 °C

Operating pressure:

max. 10 bar

Version:

with magnetic pistons and adjustable end position damping

Cylinder switch type:

D, A, Ø 125 and larger: C in combination with fastening C1 or C in combination with fastening C2

Piston diameter [mm]

32

Stroke [mm]	40
A (piston rod thread)	M 10x1,25
G (compressed air port)	G 1/8"
Repair sets	XLE 32 REP
B [mm]	12
C [mm]	30
D [mm]	19
F [mm]	22
G [mm]	26
H [mm]	120
K [mm]	3,0
M [mm]	46,5
N [mm]	32,5
CH [mm]	10
RT	M 6