

EMC XLE 40/200. ISO 15552 cylinders, piston 40 mm, stroke 200 mm, ECO

Item no. FL-XLE-40/200

Manufacturer E.MC

EAN 4050571800918

ISO 15552 cylinders, piston 40 mm, stroke 200 mm, ECO

TECHNICAL DATA

HS-Code **84123100**

Norm **ISO 15552**

Weight **1.8 kg**



STANDARDS & COMPLIANCE

ISO 15552

DESCRIPTION

Materials:

Head and base: Anodized aluminium, cylinder tube: Anodized aluminium section tube, Piston rod: Steel, hard chrome-plated, piston: Aluminium, Gasket: NBR / PUR

Temperature range:

-20 to +80 °C

Operating pressure:

max. 10 bar

Version:

with magnetic pistons and adjustable end position damping

Cylinder switch type:

D, A, Ø 125 and larger: C in combination with fastening C1 or C in combination with fastening C2

Piston diameter [mm]

40

Stroke [mm]	200
A (piston rod thread)	M 12x1,25
G (compressed air port)	G 1/4"
Repair sets	XLE 40 REP
B [mm]	16
C [mm]	35
D [mm]	21
F [mm]	24
G [mm]	30
H [mm]	135
K [mm]	3,5
M [mm]	54,0
N [mm]	38,0
CH [mm]	13
RT	M 6