

EMC XLE 50/150. ISO 15552 cylinders, piston 50 mm, stroke 150 mm, ECO

Item no. FL-XLE-50/150

Manufacturer E.MC

EAN 4050571801069

ISO 15552 cylinders, piston 50 mm, stroke 150 mm, ECO

TECHNICAL DATA

HS-Code **84123100**

Weight **2.2 kg**



STANDARDS & COMPLIANCE

ISO 15552

DESCRIPTION

Materials:

Head and base: Anodized aluminium, cylinder tube: Anodized aluminium section tube, Piston rod: Steel, hard chrome-plated, piston: Aluminium, Gasket: NBR / PUR

Temperature range:

-20 to +80 °C

Operating pressure:

max. 10 bar

Version:

with magnetic pistons and adjustable end position damping

Cylinder switch type:

D, A, Ø 125 and larger: C in combination with fastening C1 or C in combination with fastening C2

Piston diameter [mm]

50

Stroke [mm]	150
A (piston rod thread)	M 16x1,5
G (compressed air port)	G 1/4"
Repair sets	XLE 50 REP
B [mm]	20
C [mm]	40
D [mm]	27
F [mm]	32
G [mm]	37
H [mm]	143
K [mm]	3,5
M [mm]	67,0
N [mm]	46,5
CH [mm]	17
RT	M 8