

EMC XLE 80/150. ISO 15552 cylinders, piston 80 mm, stroke 150 mm, ECO

Item no. FL-XLE-80/150

Manufacturer E.MC

EAN 4050571801410

ISO 15552 cylinders, piston 80 mm, stroke 150 mm, ECO

TECHNICAL DATA

HS-Code **84123100**

Norm **ISO 15552**

Weight **4.1 kg**



STANDARDS & COMPLIANCE

ISO 15552

DESCRIPTION

Materials:

Head and base: Anodized aluminium, cylinder tube: Anodized aluminium section tube, Piston rod: Steel, hard chrome-plated, piston: Aluminium, Gasket: NBR / PUR

Temperature range:

-20 to +80 °C

Operating pressure:

max. 10 bar

Version:

with magnetic pistons and adjustable end position damping

Cylinder switch type:

D, A, Ø 125 and larger: C in combination with fastening C1 or C in combination with fastening C2

Piston diameter [mm]

80

Stroke [mm]	150
A (piston rod thread)	M 20x1,5
G (compressed air port)	G 3/8"
Repair sets	XLE 80 REP
B [mm]	25
C [mm]	45
D [mm]	33
F [mm]	40
G [mm]	46
H [mm]	174
K [mm]	4,0
M [mm]	93,0
N [mm]	72,0
CH [mm]	22
RT	M 10