

EMC ZDM 16/80 E. ISO 6432 cylinders, double acting, piston 16 mm, stroke 80 mm

Item no. FL-ZDM-16/80-E

Manufacturer E.MC

EAN 4050571930523

ISO 6432 cylinders, double acting, piston 16 mm, stroke 80 mm

TECHNICAL DATA

HS-Code **84123100**

Weight **0.15 kg**



STANDARDS & COMPLIANCE

ISO 6432

DESCRIPTION

Materials:

Head and foot: anodized aluminium, cylinder tube: 1.4301, piston rod: 1.4305, seal: NBR

Temperature range:

-20 to +80 °C

Operating pressure:

max. 10 bar

Version:

With Magnetic piston

Cylinder switch type:

D in combination with fastening D1, C in combination with fastening C1

Piston diameter [mm]	16
----------------------	----

Stroke [mm]	80
-------------	----

Version	Standard
A (piston rod thread)	M 6
B (fastening thread)	M 16x1,5
G (compressed air port)	M 5
A1 [mm]	6
C [mm]	21,8
D [mm]	12
E [mm]	6
F [mm]	16
G [mm]	82
K [mm]	22
L [mm]	17
M [mm]	111
N [mm]	9
P [mm]	56
CH [mm]	5